

setting the core dump name schema

Why would you want to change the names of the coredump from the default?

Update: this is also a very useful defence against a currently known severe security affecting bug. See Core Dump Handling Vulnerability for information and workarounds

Lets assume you got a couple of core dumps files in one directory (e.g. home) and you don't know which program caused it.

Unless you have a grsec/pax kernel with logging features enabled, it might get tricky to find out who caused the coredumps.

This is the point where the naming scheme comes handy :)

The pattern can be read/set via `/proc/sys/kernel/core_pattern`.

To set a new one just do:

```
echo "newpattern" > /proc/sys/kernel/core_pattern
```

you can have variables to make the file named different per executable, pid a.s.o..
max length 64 characters; default value is "core"

Here is a small list of possible variables

```
%p:      pid
%>NUL>:  '%' is dropped
%%:      output one '%'
%u:      uid
%g:      gid
%s:      signal number
%t:      UNIX time of dump
%h:      hostname
%e:      executable filename
%>OTHER>: both are dropped
```

If `core_pattern` does not include "%p" (default does not) and `core_uses_pid` is set, then `.PID` will be appended to the filename.

example:

```
echo "core.%e.%p" > /proc/sys/kernel/core_pattern
```

produces files names

```
core.>executable>.>pid>
```

to make the changes permanent, add the following line to `/etc/sysctl.conf`:

```
kernel.core_pattern = core.%e.%p
```

happy core dumping.

image:rdf newsfeed / //static.linuxhowtos.org/data/rdf.png (null)

|
image:rss newsfeed / //static.linuxhowtos.org/data/rss.png (null)

|
image:Atom newsfeed / //static.linuxhowtos.org/data/atom.png (null)
- Powered by
image:LeopardCMS / //static.linuxhowtos.org/data/leopardcms.png (null)
- Running on
image:Gentoo / //static.linuxhowtos.org/data/gentoo.png (null)
-
Copyright 2004-2020 Sascha Nitsch Unternehmensberatung GmbH
image:Valid XHTML1.1 / //static.linuxhowtos.org/data/xhtml1.png (null)
:
image:Valid CSS / //static.linuxhowtos.org/data/css.png (null)
:
image:buttonmaker / //static.linuxhowtos.org/data/buttonmaker.png (null)
- Level Triple-A Conformance to Web Content Accessibility Guidelines 1.0 -
- Copyright and legal notices -
Time to create this page: ms
<!--
image:system status display / /status/output.jpg (null)
-->
bodyloaded();