

Using Linux as router (mini-FAQ)

Q: is there an easy way to set the max mtu on the router side instead of setting the mtu on each machine?

A: add the following line into your /etc/ppp/ip-up script

```
/sbin/iptables -A FORWARD -p tcp --tcp-flags SYN,RST SYN -j TCPMSS
--clamp-mss-to-pmtu
```

this does the job for you.

image:rdf newsfeed / //static.linuxhowtos.org/data/rdf.png (null)

|

image:rss newsfeed / //static.linuxhowtos.org/data/rss.png (null)

|

image:Atom newsfeed / //static.linuxhowtos.org/data/atom.png (null)

- Powered by

image:LeopardCMS / //static.linuxhowtos.org/data/leopardcms.png (null)

- Running on

image:Gentoo / //static.linuxhowtos.org/data/gentoo.png (null)

-

Copyright 2004-2020 Sascha Nitsch Unternehmensberatung GmbH

image:Valid XHTML1.1 / //static.linuxhowtos.org/data/xhtml1.png (null)

:

image:Valid CSS / //static.linuxhowtos.org/data/css.png (null)

:

image:buttonmaker / //static.linuxhowtos.org/data/buttonmaker.png (null)

- Level Triple-A Conformance to Web Content Accessibility Guidelines 1.0 -

- Copyright and legal notices -

Time to create this page: ms

<!--

image:system status display / /status/output.jpg (null)

-->