

Using SSH for remote commands

This tip shows a less common use of SSH. Most people use SSH to login to servers or boxes remotely. However, you can also use SSH to issue commands on remote servers without opening a full login shell.

Note: To use SSH without having to enter a password all the time, use the passwordless login tutorial in the "Security" section.

To issue commands through SSH, simply type the command after the normal SSH login information (e.g. `ssh user@host command`). The following example shows you how to view log files on a remote web server.

Code Listing 1: Viewing an Apache2 access_log

```
% ssh david@www.example.com tail /var/log/apache2/access_log
```

Alternatively, you could change passwords over SSH (although using public key authentication with SSH is recommended over passwords).

Code Listing 2: Remotely changing a password

```
% ssh david@example.com passwd
(current) UNIX password: password
New UNIX password: new_password
Retype new UNIX password: new_password
Changing password for david
```

This should get you started with remote command execution. See the SSH man pages for more options.

From <http://www.gentoo.org/news/en/gwn/20030908-newsletter.xml>

image:rdf newsfeed //static.linuxhowtos.org/data/rdf.png (null)

|
image:rss newsfeed //static.linuxhowtos.org/data/rss.png (null)

|
image:Atom newsfeed //static.linuxhowtos.org/data/atom.png (null)

- Powered by

image:LeopardCMS //static.linuxhowtos.org/data/leopardcms.png (null)

- Running on

image:Gentoo //static.linuxhowtos.org/data/gentoo.png (null)

-

Copyright 2004-2020 Sascha Nitsch Unternehmensberatung GmbH

image:Valid XHTML1.1 //static.linuxhowtos.org/data/xhtml1.png (null)

:

image:Valid CSS //static.linuxhowtos.org/data/css.png (null)

:

image:buttonmaker //static.linuxhowtos.org/data/buttonmaker.png (null)

- Level Triple-A Conformance to Web Content Accessibility Guidelines 1.0 -

- Copyright and legal notices -

Time to create this page: ms

```
<!--  
image:system status display / /status/output.jpg (null)  
-->  
bodyloaded();
```